## What is claimed is:

5

\*\*\*

TE

15

20

10

- A nail holder strip, having a plurality of nail holders comprising,
   a support base, for holding and supporting a nail;
   a passage in said support base, for receiving said nail
   therethrough;
  - a stiffening stem positioned adjacent to said passage and to said support base, so as to provide additional rigidity to the strip; and

wherein each of said plurality of nail holders is releasably attached to form said nail holder strip.

- The nail holder strip according to claim 1, further comprising a
  protrusion within said passage, so as to provide a releasable
  frictional hold on said nail.
- 3. The nail holder strip according to claim 2, wherein said protrusion within said passage in at least one of said plurality of nail holders is positioned in an opposite position in relation to said protrusion within said passage in an adjacent nail holder of said plurality of nail holders forming said nail holder strip.

- 4. The nail holder strip according to claim 2, wherein said passage is semi-circular.
- 5 5. The nail holder strip according to claim 2, wherein said protrusion includes a flat surface.
  - 6. The nail holder strip according to claim 1, wherein said stiffening stem includes a plurality of stiffening stems positioned adjacent to said passage and to said support base.
- The nail holder strip according to claim 6, wherein said plurality of stiffening stems are on opposite sides of said passage.
- 15 8. The nail holder strip according to claim 6, further comprising a brace adjacent to said support base and at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems.
- The nail holder strip according to claim 8, wherein said brace 20 9. includes a plurality of braces adjacent to said support base, and

I and

said at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems.

- The nail holder strip according to claim 6, further comprising a breakable bridge between each of said plurality of nail holders, wherein said breakable bridge is attached to at least one of said plurality of stiffening stems.
  - 11. The nail holder strip according to claim 1, wherein said passage includes a first portion and a second portion, and wherein said first portion and said second portion have different diameters.
- 12. The nail holder strip according to claim 1, further comprising a

  brace adjacent to said support base and said stiffening stem, so as
  to reinforce or stabilize said stiffening stem.
  - 13. The nail holder strip according to claim 12, wherein said brace includes a plurality of braces adjacent to said support base and said stiffening stem, so as to reinforce or stabilize said stiffening stem.

10

erit:

### ### ####

15

20

- 14. The nail holder strip according to claim 1, further comprising a breakable bridge between each of said plurality of nail holders.
- 5 15. The nail holder strip according to claim 14, wherein said breakable bridge is attached to said support base.
  - 16. A nail holder strip, having a plurality of nail holders comprising, a support base, for holding and supporting a nail; a passage in said support base, for receiving said nail therethrough;

a stiffening stem positioned adjacent to said passage and to said support base, so as to provide additional rigidity to the strip;

a protrusion within said passage, so as to provide a releasable frictional hold on said nail; and

wherein each of said plurality of nail holders is releasably attached to form said nail holder strip.

17. The nail holder strip according to claim 16, wherein said protrusion within said passage in at least one of said plurality of nail holders is positioned in an opposite position in relation to said protrusion

within said passage in an adjacent nail holder of said plurality of nail holders forming said nail holder strip.

- 18. The nail holder strip according to claim 16, wherein said passage is semi-circular.
- 19. The nail holder strip according to claim 16, wherein said protrusion includes a flat surface.
- 20. The nail holder strip according to claim 16, wherein said stiffening stem includes a plurality of stiffening stems positioned adjacent to said passage and to said support base.
- 21. The nail holder strip according to claim 20, wherein said plurality of stiffening stems are on opposite sides of said passage.
  - 22. The nail holder strip according to claim 20, further comprising a brace adjacent to said support base and at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems.

5

12.

The state of the s

15

- 23. The nail holder strip according to claim 22, wherein said brace includes a plurality of braces adjacent to said support base, and said at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems.
- 24. The nail holder strip according to claim 20, further comprising a breakable bridge between each of said plurality of nail holders, wherein said breakable bridge is attached to at least one of said plurality of stiffening stems.
- 25. The nail holder strip according to claim 16, wherein said passage includes a first portion and a second portion, and wherein said first portion and said second portion have different diameters.
  - The nail holder strip according to claim 16, further comprising a 26. brace adjacent to said support base and said stiffening stem, so as to reinforce or stabilize said stiffening stem.

THE STATE OF

ns is

Est. THE STATE OF THE S

- 27. The nail holder strip according to claim 26, wherein said brace includes a plurality of braces adjacent to said support base and said stiffening stem, so as to reinforce or stabilize said stiffening stem.
- 28. The nail holder strip according to claim 16, further comprising a breakable bridge between each of said plurality of nail holders.
- 29. The nail holder strip according to claim 28, wherein said breakable bridge is attached to said support base.
- 30. A nail holder strip, having a plurality of nail holders comprising, a support base, for holding and supporting a nail; a passage in said support base, for receiving said nail therethrough;

a stiffening stem positioned adjacent to said passage and to said support base, so as to provide additional rigidity to the strip;

a protrusion within said passage, so as to provide a releasable frictional hold on said nail;

5

10

15

20

5

wherein said protrusion within said passage in at least one of said plurality of nail holders is positioned in an opposite position in relation to said protrusion within said passage in an adjacent nail holder of said plurality of nail holders forming said nail holder strip; and

wherein each of said plurality of nail holders is releasably attached to form said nail holder strip.

31. A nail holder strip, having a plurality of nail holders comprising,

a support base, for holding and supporting a nail;

a passage in said support base, for receiving said nail therethrough;

a plurality of stiffening stems positioned adjacent to said passage and to said support base, so as to provide additional rigidity to the strip;

a brace adjacent to said support base, and at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems; and

wherein each of said plurality of nail holders is releasably attached to form said nail holder strip.

32. The nail holder strip according to claim 31, further comprising a protrusion within said passage, so as to provide a releasable frictional hold on said nail.

5

10

- 33. The nail holder strip according to claim 32, wherein said protrusion within said passage in at least one of said plurality of nail holders is positioned in an opposite position in relation to said protrusion within said passage in an adjacent nail holder of said plurality of nail holders forming said nail holder strip.
- 34. The nail holder strip according to claim 32, wherein said passage is semi-circular.
- 15 35. The nail holder strip according to claim 32, wherein said protrusion includes a flat surface.
  - 36. The nail holder strip according to claim 31, wherein said plurality of stiffening stems are on opposite sides of said passage.

- 37. The nail holder strip according to claim 31, wherein said brace includes a plurality of braces adjacent to said support base, and said at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems.
- 38. The nail holder strip according to claim 31, further comprising a breakable bridge between each of said plurality of nail holders, wherein said breakable bridge is attached to at least one of said plurality of stiffening stems.
- 39. The nail holder strip according to claim 31, wherein said passage includes a first portion and a second portion, and wherein said first portion and said second portion have different diameters.
- 40. The nail holder strip according to claim 31, further comprising a breakable bridge between each of said plurality of nail holders.
- 20 41. The nail holder strip according to claim 40, wherein said breakable bridge is attached to said support base.

THE REAL PROPERTY OF THE PARTY OF THE PARTY

THE STATE OF

42. A nail holder strip, having a plurality of nail holders comprising, a support base, for holding and supporting a nail; a passage in said support base, for receiving said nail therethrough;

a plurality of stiffening stems positioned adjacent to said passage and to said support base, so as to provide additional rigidity to the strip;

a plurality of braces adjacent to said support base, at least one of said plurality of stiffening stems, so as to reinforce or stabilize said at least one of said plurality of stiffening stems; and

wherein each of said plurality of nail holders is releasably attached to form said nail holder strip.